



LED Lighting | Forged in America™

# 4' T8 Integral Plastic Tube

2000 lms | 120-277VAC | Part T8BP-4-20-840-MV

- > Base G13 Bi-Pin
- > All Plastic Housing
- > FR4 PCB Board
- > Cool White 4000k CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free - No Bulb Replacements
- > 5 Year Limited Warranty



## Custom Engineered for Correctional Facilities

(No Glass or Aluminum PCB that can be “weaponized”)

### SPECIFICATIONS

Description	4' T8 Integral Plastic Tube
Input Voltage (VAC)	120-277
Wattage	15
Dimmability	Non-Dimmable
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	2000
CCT <sup>3</sup>	4000k
Location Rating	UL Damp
CRI <sup>4</sup>	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 115°F (45° C)
Power Factor	>0.9
R9	NA
DUV	NA
Operating Frequency (Hz)	50/60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

## New for 2019 The Ultimate “PRISON” TUBE

[www.IndependenceLED.com](http://www.IndependenceLED.com)

**Contact:**

Charlie Szoradi

[Charlie@IndependenceLED.com](mailto:Charlie@IndependenceLED.com)

610-551-5224

Manufacturing Partner: ETi SSL

HAZARD PREVENTION TUBE





LED Lighting | Forged in America™

# 4' T8 Integral Plastic Tube

2000 lms | 120-277VAC |

Special Order lengths and color temperatures are available upon request.

HAZARD PREVENTION TUBE

## SHIPPING INFORMATION

Part	T8BP-4-20-840-MV
UPC	849489060866
Product Dimensions (L x W x H in.)	47 1/8 x 1 1/8 x 1 1/8
Product Dimensions (L x W x H cm.)	120 x 3 x 3
Product Weight (lbs.)	0.51
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	24
Master Carton Bar Code	50849489060861
Master Carton Dimensions (L x W x H in.)	50.43 x 9.84 x 6.93
Master Carton Dimensions (L x W x H cm.)	128.1 x 25.0 x 17.6
Master Carton Weight (lbs)	15.64
Pallet Quantity	864

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

[www.IndependenceLED.com](http://www.IndependenceLED.com)

**Contact:**

Charlie Szoradi

[Charlie@IndependenceLED.com](mailto:Charlie@IndependenceLED.com)

610-551-5224

Manufacturing Partner: ETi SSL

